

1.3 MP AHD IR Bullet Kamera



Ürün Özellikleri	Açıklama	DataSheet
Sensor	1/3" 1.3 Mega Pixel CMOS	
Min.Illumination	0.06Lux @(F1.2,AGC ON) ,0 Lux with IR	
Shutter time	1/25s ~ 1/100,000s	
S/N (Y signal)	52dB (AGC Off, Weight On)	
Image Resolution	960P (1280x960)	
Frame Rate	30 fps (60 Hz), 25fps (50Hz)	
Minimum Illumination	0.01Lux	
Day/Night Mode	ICR-IR cut filter	
Number of IR LEDs	12pcs IR LED Laser	
Infrared Illumination	Visible up to 98' (30m)	
Lens Mount	2.8-12mm	
Backlight Compensation	BLC/HLC, backlighting setup, off	
White Balance	Auto, Manual, Fluorescent light, Incandescent lamp, Sunlight, Flash lamp, Cloudy and Shadowy	
DNR	3D-DNR	
Transmission Distance	Over 500m via 75-3 coaxial cable	
Video Output	1ch AHD (1.0Vp-p, 75Ω), remote storage at IE client	
Power	12V DC	
Power Consumption	350mA (IR on max 650mA)	
Operating Temperature	10~ +50 Deg C. RH 95% Max.	
Storage Temperature	20~ +60 Deg C. RH 95% Max.	
Waterproof	Yes	
Video Out	1.0V p-p 75Ω, BNC Connector	
Dimensions(WxD)	268.7mmx108.4mmx89.9mm	
Weight	780g	
Material	Aluminum Alloy	