



P Series IP Camera

OND-P3621-MZ



| | |
|--------|--|
| Series | P Series 2MP, H.265, Motorize Zoom Lens, 120dB WDR, Dome Type |
|--------|--|

Camera

| | |
|--------------------|--|
| Image Sensor | 1 / 2.7 "CMOS |
| Image Size | 1920 x 1080 |
| Electronic Shutter | 1 / 25 s ~ 1 / 100000 s |
| Iris Type | Fixed Iris |
| Min. Illumination | 0.05 lux @F1.2,AGC ON; 0 lux with IR |
| Lens | 2.8 ~ 12 mm(AZ) @F1.4, horizontal field of view : 109.8° ~ 38.5° |
| Lens Mount | Ø14 |
| Day & Night | ICR |
| Wide Dynamic Range | 120dB |
| Digital NR | 3D DNR |
| Angle Adjustment | Pan : 0°~360°, Tilt : 0°~90°, Rotation : 0°~360° |

Image

| | |
|-------------------|--|
| Video Compression | H.265+ / H.264 / MJPEG |
| H.265 Compression | Main Profile @Leve4.1 High Tier |
| Resolution | 1080P (1920 x 1080), 720P (1280 x 720),D1, CIF, 480 x 240 |
| Main Stream | 60Hz : 1080P (1 ~ 30 fps) / 720P (1 ~ 30 fps) 50Hz : 1080P (1 ~ 25 fps) / 720P (1 ~ 25 fps) |
| Bit Rate | 128 Kbps ~ 6 Mbps |
| Bit Rate Type | VBR / CBR |
| Quality | Five levels under VBR; Freely adjustable under CBR |
| Image Settings | ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, sharpen, NR, etc. adjustable through client software or web browser |
| ROI | Each ROI to be configured separately |

Interfaces

| | |
|--------------|------------------------------|
| Network | RJ45 |
| Audio | MIC IN x 1 |
| Video Output | CVBS video output (BNC x 1) |

Functions

| | |
|--------------------|--|
| Remote Monitoring | IE browsing,CMS remote control |
| Online Connection | Support simultaneous monitoring for up to 4 users ; Support multi-stream real time transmission |
| Network Protocol | TCP / IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS,SMTP,FTP |
| Interface Protocol | ONVIF, GB-T / 28181 - 2011 |
| Storage | Network remote storage |
| Smart Alarm | Motion alarm |
| Smart Analysis | Object removal detection, line crossing detection and intrusion detection, etc. |
| Corridor Mode | Yes |
| PoE | Yes |
| IR Distance | 30 ~ 50m |
| Ingress Protection | IP66,IK10 |

Others

| | |
|-----------------------|--|
| Power Supply | DC12V / PoE |
| Power Consumption | < 2W |
| IR Consumption ON | < 4.5W |
| Operating Environment | - 20 °C ~ 50 °C, 10 % ~ 90 % relative humidity |
| Dimensions (mm) | Ø109 x 130 |
| Weight (net) | 701g |
| Installation | Pendent mounting |

2 MP Network IR Water-proof Motorize Zoom Dome Camera



Features

- * 1080P (1920 x 1080) full real time coding
- * Max.resolution : 1920 x 1080
- * ICR auto switch, true day / night
- * 30 ~ 50 m IR night view distance
- * 3D DNR, physical WDR
- * Smart analysis including object removal, line crossing detection and intrusion detection, etc.
- * ROI coding
- * Support CVBS video output and one-way audio
- * PoE power supply
- * Support smart phone, iPad, remote monitoring
- * Support P2P
- * IP66 ingress protection
- * Support three streams

